

SHORT REACH HANDLE LEVER

CODE	
APPLICATION	CL250 (MC57) / CBR250R / CB250F (MC41/43) / CB250R (MC52) / CB125R (JC79) / MONKEY125 (JB02/03) / GROM (JC61/75/92)

Thank you for purchasing Kitaco product.
Read and understand the instruction before installing.

ATTENTION (MUST READ)

- Brake related parts is important. If installation is failed, it may directly cause of accident. Please be careful of installing and handling.
- Do not modify the way which is not listed or it will cause damage and trouble.
- We are not responsible for violation of law or damages and accidents caused by assembling mistake and improper setting.
- Please ask authorized mechanic for assembling and setting. Ask a specialist at specialty shop if you do not understand the role of the surrounding parts.
- Refer to the manufacturer service manual when installation.
- Bolts and nuts may get loosen by engine vibration. Make sure not to loosen any bolts and nuts before driving.

- Basically, reuse stock parts if it is unattached.
If there is a hard degradation like a blem, fatigue and wear etc on the reuse parts, please change to new ones.
- Hold pivot bolt and tighten nut with specified torque.
PIVOT BOLT : TORQUE : 1.0Nm (0.1kgfm) *Apply grease.
PIVOT NUT : TORQUE : 5.9Nm (0.6kgfm)

△ ATTENTION (GRIP WIDTH ADJUSTMENT)

By installing this product, grip and lever width is closer, stock grip width (play) might touch the grip and unable to operate correctly. Please adjust each lever grip width (play) before riding.

ABOUT BRAKE LEVER

Use this product with mechanical trouble of caliper and master cylinder with wearing brake pad, or neglect fluid maintenance might touch grip easily, it is dangerous. Check and maintenance each part regularly.

